

1261-62A SHOE

GENERAL NOTES:

- *1. LOCATE CLOSER & SHOE FROM CENTERLINE OF PIVOT OR SWING CLEAR HINGE PIN WHEN USED.
- **2. THIS DIMENSION IS ALWAYS FROM THE SAME SURFACE AS THE SHOE IS MOUNTED ON.
- 3. TOP RAIL LESS THAN 6 1/2" REQUIRES A DROP PLATE.
- 4. THE AUXILIARY STOP IS SHOWN FOR REFERENCE ONLY. THIS TEMPLATE MAY BE USED TO PROVIDE CLEARANCE FOR OTHER TYPES OF HARDWARE SUCH AS COORDINATORS, SOUND SEALS ETC.
- 5. REINFORCING PER ANSI/SDI-100 RECOMMENDED FOR HOLLOW METAL DOORS AND FRAMES.
- 6. CLOSER SIZE IS 10" x 2 1/4" x 2 7/8".

ATTENTION:

STOP WIDTH 1 1/4" TO 3 1/4" MOUNT SHOE IN RABBET BEHIND STOP.

STOP WIDTH OVER 3 1/4" MOUNT SHOE TO STOP FACE NO CLOSER THAN 1 1/4" TO DOOR FACE.
USE THE FIVE MOUNTING SCREWS PROVIDED.

